

F5-24

F5-24

Product Description

The Schaefer F5™ livestock fan is a high velocity circulation fan designed to provide the ideal environment for maximum show animal comfort and hair growth. Built to withstand the impact of show travel, the F5 comes with dependable, long lasting motor and guards for extreme durability.

Features

Industry leading airflow and air velocity to keep livestock cool and maximize hair growth

Heavy-duty steel guards with reinforced ribs and outer rings, built to withstand the impact of show travel

Powder coated black finish over guards for stylish appearance to blend with show displays

Corrosion resistant inside and out for durability and long life

Powerful motors with unique low solidity ratio blade for best-in-class efficiency and quiet operation without sacrificing airflow and speed

Flexible, 7 foot cord with water resistant and weather proof on/off switch for convenient operation

Hang mount included for easy set-up and take-down

Two year warranty

Made in the USA



Specifications

Blade Color	Metallic
Brand	Schaefer
Cfm (free Air)	7680
Rpm 60 Hz Motor	1550-1800
Drive	Direct
Enclosure	TEAO
Frame Size	48Z
Phase	1
Speeds	1
Vfd Compatible	No
Cfm/watt (free Air)	15.6

SIGN UP!

Frequency (hz)	60/50
Guard Color	Black
Nameplate Amps	4.8/2.4
Number Of Wings	3
Bess Lab Performance Test #	13214
Power (hp)	1/2
Product Dimensions (L X W X H Inches)	25.75" x 14.25" x 28.375"
Product Net Weight (lbs)	40

Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Pallet Quantity	20
Product Color	Black
Product Shipping Dimensions (in)	26 x 26 x 18
Speed Control Compatible?	Yes
Cfm Range (free Air)	5001 - 10000
Cord Length (feet)	7
Fixed Or	Fixed

Cord	Included - Wired
Diameter (inches)	24

Switch	On cord
Voltage	115/230
Maximum Rpm	1725
Air Velocity (@ 5 Times Diameter)	1240
Blade Material	Aluminum

Portable	
Guard Material	Powder Coated Steel
Oscillating	No
Rpm 50 Hz Motor	1350-1500
Country Of Origin	US
Guard Spacing (inches)	1/2 OSHA

SIGN UP!