SCHAEFER®

VK12-GA

VK12-GA



Product Description

Reduce heat stress and improve air quality with Schaefer's uniquely designed circulation fans. Unrivaled in the market, these fans are engineered to produce greater air movement and superior cooling no matter the application. You don't hear them. You don't see them. You only feel them!

Also known as Horizontal Air Flow (HAF) fans, these fans move air in a coherent horizontal pattern creating a gentle 'racetrack' air flow pattern needed in greenhouses to maximize heat distribution and humidity control by mixing the air, from ceiling to floor.

Features

Deep guard design for unmatched performance, low noise levels and safety without sacrificing airflow

Matched high quality motors and blades for maximum efficiency

Powder coated steel guards for increased durability and corrosion resistance

Hot dipped galvanized guards on VK12-GA and VK20-GA models for even greater rust protection

Powder coated steel mounting bracket and power cord included

Wide variety of mounting options available for flexible and easy installation

Variable speed controls available

Misting kits available for even greater cooling

Two year warranty

Specifications

Air Velocity (@ 10')	TBD
Blade Color	Metallic
Brand	Schaefer
Cfm (free Air)	1470
Drive	Direct
Mount Included	VS12FMT
Phase	1
Speeds	1
Vfd Compatible	No
Cfm/watt (free Air)	14

Mount Type Included	Ceiling
Nameplate Amps	1.3/.65
Number Of Wings	3
Bess Lab Performance Test #	12370
Power (hp)	1/10
Product Net Weight (lbs)	20
Switch	Not included
Voltage	115/230

Speed Control Compatible?	Yes
Able To Ship Small Parcel	Yes
Cfm Range (free Air)	1001 - 2500
Cord Length (feet)	5
Distinguishing Feature	Highly Corrosion Resistant
Fixed Or Portable	Fixed
Guard Material	Galvanized Steel

Cord	Included - Not Wired
Diameter (inches)	12
Frequency (hz)	60
Guard Color	Metallic

SIGN UP!

mum Rpm	1725
Air Velocity (@ 5 Times Diameter)	680
Blade Material	Aluminum
Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Product Color	White
Product Shipping Dimensions (in)	15 x 15 x 17

Oscillating	No
Country Of Origin	US
Guard Spacing (inches)	1/2 - 1 UL507
Cfm/watt (@0.10")	TBD
Cfm/watt (@0.05")	TBD