

VK36-3

VK36-3

Product Description

These durable and aesthetically pleasing fans feature a high airflow with a wide airflow pattern, reducing the number of fans needed for complete coverage.

Features

Powerful ½ hp motor provides high airflow with a wide airflow pattern for excellent coverage

High-density polyethylene housing for superior corrosion and moisture resistance, wide temperature range capability and high stress crack, wear and abrasion resistance

Wide-spaced steel guards dipped in zinc and powder coated for superior corrosion resistance

Matched thermally protected TEAO motors and blades for high performance and long life

19" T-shaped, powder-coated steel fan ceiling mount included

Two year warranty

Made in the USA



Specifications

Blade Color	Gray
Brand	Schaefer
Cfm (free Air)	11380
Rpm 60 Hz Motor	800-900
Drive	Direct
Enclosure	TEAO
Frame Size	48YZ
Housing Material	Polyethylene
Mount Included	VS36FMT
Phase	3
Speeds	1
Vfd Compatible	No
Cfm/watt (free Air)	27.6
Cord	Not included

Diameter (inches)	36
Frequency (hz)	60/50
Guard Color	White
Mount Type Included	Ceiling
Nameplate Amps	2.3/1.2
Number Of Wings	3
Bess Lab Performance Test #	8059
Power (hp)	1/2
Product Net Weight (lbs)	59
Switch	Not included
Voltage	230/460

Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Pallet Quantity	5
Product Color	White
Product Shipping Dimensions (in)	38 x 39 x 17
Speed Control Compatible?	No
Cfm Range (free Air)	10001 - 15000
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel
Oscillating	No
Rpm 50 Hz Motor	700-800

SIGN UP!



Maximum Rpm	825
Air Velocity (@ 5 Times Diameter)	730
Blade Material	Galvanized Steel

Country Of Origin	US
Guard Spacing (inches)	1/2 - 1 UL507
Housing Color	White