SCHAEFER®

VKM42-2-O

VKM42-2-O

Product Description

Tired of continually replacing your mobile drum fans? Schaefer mobile drum fans have “Schaefer-Tough” polyethylene housing and durable reinforced galvanized steel wheel carriage for impact and rust resistance. These fans are built to last, the best looking fans in the industry and move massive amounts of air at high velocities. A single “Schaefer-Tough” mobile fan will not only take the place of several lower performance fans, but out live them as well, lasting for 10+ years.

Features

High-density polyethylene housing for superior impact, abrasion and temperature-cracking resistance

Galvanized steel base for complete corrosion resistance inside and out

Narrow fan profile, and ergonomic pull and base handles for easy portability

Large rubber wheels mounted inside the fan profile for convenience and safety

Stacking tabs for storage and transportation savings included on OSHA VKM models, optional on others

OSHA compliant guard

Two year warranty

Made in the USA

Specifications

Blade Color	Gray
Brand	Schaefer
Rpm 60 Hz Motor	1550-1800
Drive	Belt
Enclosure	TEAO
Frame Size	56
Housing Material	Polyethylene
Phase	1
Speeds	2
Vfd Compatible	No
Cfm/watt (free Air)	14.7
Cord	Included -

Guard Color	White
Nameplate Amps	12.3
Number Of Wings	3
Bess Lab Performance Test #	14024
Power (hp)	1 1/3
Product Net Weight (lbs)	140
Switch	On product
Voltage	115
Maximum Rpm	1725
elocity (@ 5 s Diameter)	380

Product Shipping Dimensions (in)	47 X 47 X 36
Speed Control Compatible?	No
Able To Ship Small Parcel	No
Cfm (low)	10900
Cfm Range (free Air)	15001 - 20000
Cord Length (feet)	12
Fixed Or Portable	Portable
Guard Material	Powder Coated Steel
Oscillating	No

SIGN UP!

	Wired
Diameter (inches)	42
Frequency (hz)	60

Blade Material	Galvanized Steel
Cfm (high)	16600
Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Product Color	White

Rpm 50 Hz Motor	1000-1200
Country Of Origin	US
Guard Spacing (inches)	1/2 OSHA
Housing Color	White

SIGN UP!